



Bezel	
L/R/Top/Down	12.7/12.7/12.7/17.3mm

Thickness	73 mm
-----------	-------

Dimension (WxHxD)	
VESA Dimension (WxH)	200*200 (M6)
Unit W/stand	1124*703*249 mm
Unit W/O stand	1124*656*73 mm
Master Carton	1240*790*150mm

Weight (N.W.)	
Unit W/stand	11.4 KG
Unit W/O Stand	11.2 KG
Unit W/stand W/Master Carton	17 KG

Container Loading(unit)	
20' GP Container Unit Load w/o Pallet	130
40' GP Container Unit Load w/o Pallet	278
40' HQ Container Unit Load w/o Pallet	417

Video Connections	Quantity
 Analog&Digital TV Tuner	1
 HDMI 2.0	3
 Component Input (Y,Cb,CrY,Pb,Pr)	1(Y terminal will be the same)
 VGA Input (15 pin D-Sub)	N/A
 USB	2
 RJ45	1
 TF	N/A
 Composite Video Input	1

Audio Connections	Quantity
 Stereo Mini Phono Jack Input (3.5mm)	N/A
 Headphone: Stereo Mini (3.5mm)	1
 RCA Input	×1(R/L)
 Optical Digital Output	1

TV Reception	
TV System	ATSC/NTSC M
Tuner receiving range	CH2~CH69 AIR/CH1~CH135 CABLE
Antenna Impedance	75 ohm
Connector type	F

Accessories in the box	
Remote control/Battery	
Stand/Screws	
Quick Connect Guide/User manual/Warranty card	

\	
\	
\	
\	

Display Features	
Screen Size/Panel Vendor	49.5inch/TBD
Display Type	LED
Aspect Ratio	16:9
Panel Resolution	3840 x 2160
Brightness	220 ~ 270 cd/m ²
Contrast Ratio	3500 ~ 5000:1(Typical)/TBD
Viewing Angle	176°(H) x 176°(V)(CR≥10)/TBD
Response Time Gray-Gray	9.5ms/TBD
Backlight Life	> 30000 hrs
Panel Refresh Rate	60HZ
Max. Color	16.7M

HDMI Resolutions Supported	
	640 x 480 @ 60Hz/70Hz/75Hz
	800 x 600 @ 60Hz/70Hz/75Hz
	1024 x 768 @ 60Hz/70Hz/75Hz
	1280 x 1024 @ 60Hz
	1360 x 768 @ 60Hz (HD)
	1920 x 1080 @ 60Hz (FULL HD)
	3840 x 2160@ 30HZ/60HZ(Ultra-HD)

Features	
Built in 3D PAL/NTSC Comb Filter/Built in BTSC/SAP, built-in 3D Video Noise Reduction	
Over-The-Air ATSC/NTSC RF Input Support	
Digital/Analog Channel auto tuning	
Support V-CHIP/CCD/Favorite Channel Edition/TTS	
Component &HDMI support :480i,576i,480P,576P,720P,1080i ,1080P(Only HDMI support 4K2K, HDMI 2.0 supports 4K2K 60Hz) HDMI Surpport ARC	
Android 7.x, pre-load Google play Store, Google play Movies &TV,YouTube, Netflix,Newsy,Hulu etc. Support TTS/AD	
WIFI 802.11a/g/n/ac (2.4GHz/5GHz)	Bluetooth 4.1
CPU/GPU: CA53*4/Mali-T820MPX	
Android 7.1 / Voice control with BLT	
DDR/eMMC: 2G+16G	
OSD Language:English, French, Spanish	
Certification: ETL,FCC, CEC(no Energy star), WIFI	
USB Surpport File Format:Upgrade,Gaming controllers,Keyboards and computer mouse devices	

Electronics	
Solution	Mstar MSD8688
Maximum Audio Output	2x8 W(L/R)

Power Requirements	
Power Source	AC 100 ~ 240V 50/60Hz
Unit input power	150W
Standby consumption	< 0.5 W

Environment	
Operating Temperature	5°C ~ 35°C
Operating Humidity	20% ~ 80%
Storage Temperature	\
Storage Humidity	\