

GPAWC72W

USB-C 72W 4-Port Charger [USB-IF]

- Centralized charging station for your USB mobile devices
- Charge (1) USB-C and (3) USB-A devices simultaneously
- Intelligent design provides just the right power for your devices
- Built-in protection against overcurrent and overvoltage
- Full range 100-240VAC voltage support



Charge Multiple Devices Simultaneously

Charge up your most power-hungry USB-C devices such as a laptop, smartphone or tablet and up to three (3) USB-A peripherals with IOGEAR's USB-C 72W 4-Port Charger. This flexible, portable charger plugs into any standard outlet and is perfect for use anywhere you want to charge multiple devices at the same time.

Big Power in a Compact Design

The USB-C 72W 4-Port Charger accommodates the power demands of USB-C devices such as a laptop or tablet with a charging capacity of up to 60W on its single port. Power up to three (3) USB-A devices simultaneously with a maximum charging capacity of 12W for the ultimate in charging efficiency. With its compact design, the 4-port charger easily finds a home on the kitchen counter, nightstand, in the office or on the road with you.

Perfect for your Modern Mobility Devices

- Centralized charging station for your USB mobile devices
- Charge (1) USB-C and (3) USB-A devices simultaneously
- Intelligent design provides just the right power for your devices
- Built-in protection against overcurrent and overvoltage
- Full range 100-240VAC voltage support
- Compatible with most USB-C devices
- 1x USB-C port provides a total of 60W (5V/9V/12V/15V/20V @ 3A max) power
- 3x USB-A ports provide total of 12W (5V @ 2.4A max) power
- USB-IF Certified











Requirements Package Contents

15.75" (40cm)

13.39" (34cm)

10.24" (26cm)

20.5lb (9.3kg)

4.85 lb (2.2kg)

0.75lb (0.34kg)

0.65lb (0.29kg)

24

- Device powered via USB-C / USB-A
- 1 x GPAWC72W
- 1 x Warranty Guide

Function	GPAWC72W	Dimensions	GPAWC72W
Environment		Unit Dimensions	
Humidity	5% ~ 90% RH	Height	2.83" (7.2 cm)
Operation Temperature	0~40°C	Depth	1.06" (2.7 cm)
Storage Temperature	-20 ~ 80°C	Length	3.54" (9cm), AC Cord: 48"
Max Output Power	72W	Inner Pack	
Power Input Rating		Width	4.72" (12cm)
Unit Power	100-240VAC 50/60Hz	Height	6.3" (16cm)
Power Output Rating		Length	15" (38cm)
Total DC Power Output	USB A: 5V/2.4A ; USB-C: 5V,9V,12V,15V,20V/3A	Inner Pack Qty.	6
Power Management	3V,3V,12V,13V,2UV/3M	Unit Package Dimensions	
	A Port: >=80% ; C Port: >=81.4%	Width	2.36" (6cm)
Efficiency	<=250mV	Height	5.67" (14.4cm)
Ripple Noise		Length	4.33" (11cm)
Warranty	1-Year	Master Carton	

Width

Height

Depth

Weight

Master Carton Qty.

Master Carton Wt.

Inner Pack Wt.

Unit Pack Wt.

Unit Wt.