

GSX 1200 PRO

Audio amplifier designed for competitive gaming

Designed for the driven team gamer, up to eight GSX 1200 PRO Audio Amplifiers can be connected together for the ultimate in hard-wired lag-free communication and control of inbound and outbound chat. An inbound microphone gain wheel and separate control of the loudness of your own voice in your headset delivers focus on game chat for on-the-fly strategy discussions.

A proprietary 7.1 Virtual Surround Algorithm developed for competitive gamers provide the ultimate in spatial awareness and positional gaming audio. Precise control of both game and chat audio is provided by separate adjustment of – and one touch switching – between headphones and speakers. Lock your audio configurations settings to prevent accidental changes and dominate with precision audio cues and ultimate audio control.

See more at eposaudio.com/gsx-1200



Key benefits & features

Dominate with audio

Dominate your game with the GSX 1200 PRO Audio Amplifier with 7.1 surround sound and separate audio and inbound/outbound chat control.

Binaural Rendering Engine – 7.1 surround

Delivers exceptional spatial awareness and positional game audio

Chain up to eight GSX 1200 PRO Amplifiers

Hard wire your amplifiers for ultimate lag free team communication

Built in DAC and EQ modes

Get precise control of your game audio with a dedicated DAC chip and EQ presets

Separate control for game audio and chat

Focus on game chat when needed for collaborative in-game strategizing

GSX 1200 PRO

Product data

General

USB standard	USB 2.0 full speed & USB audio 1.0
Total harmonic distortion	0.005 % THD @ -3dBFS
Cable length	USB cable: 1.2 m Chat cable: 2.0 m
Connector plugs	mini-USB socket 3.5 mm headset socket 3.5 mm microphone socket 3.5 mm loudspeaker socket 2.5 mm chat interface socket A 2.5 mm chat interface socket B
Compatibility	PC & Mac®
Warranty	2 years, international

Supported sample rates

Main Audio	71: 44.1 kHz @ 16 bit 71: 48.0 kHz @ 16 bit 2.0: 44.1 kHz @ 16 bit 2.0: 48.0 kHz @ 16 bit
Main Audio HD	2.0: 96.0 kHz @ 24 bit
Communication Audio	1.0: 16.0 kHz @ 16 bit

Audio outputs

Headphones – Frequency response – Recommended headphone impedance – Max. output voltage	DC coupled & dual rail power supply 0 – 48.0 kHz 16 – 150 Ω 1 V RMS @ 32 Ω
Line out (AUX) – Frequency response – Max. output voltage	1.5 Hz – 48.0 kHz 1 V RMS @ 10 Ω

Packaging

Dimension of product packaging (L x W x H)	145 x 70 x 140 mm
Package weight (incl. complete product and packaging)	410 g
Dimension of master carton (L x W x H)	415 x 460 x 160 mm
Units in distributor master carton	10
Languages	English, German, French, Spanish, Italian, Dutch and Portuguese

Content of delivery	
What's in the box	USB cable, Chat cable, Quick Start Guide, Safety Guide

GSX 1200 PRO

Product overview

Product	Art. no.	Description	EAN / UPC code
GSX 1200 PRO	1000239	USB audio amplifier for gaming	EAN: 57 14708 00038 9 UPC: 8 40064 40038 1

Spare parts/Accessories

Product	Art. no.	Description	EAN / UPC code
Chat Link Cable	507231	Cable for conneting Chat Link	EAN: 40 44155 22267 8 UPC: 6 15104 29971 9

