## Features and Technical Specifications

## Alienware 25 Gaming Monitor

Display

Viewable image size (diagonal)

Active display area (horizontal x vertical)

Panel technology

Display screen coating

Maximum preset resolution

Typical viewing angles (vertical / horizontal)

Pixel pitch and Pixels-Per-Inch (PPI)

Aspect ratio

**Brightness (typical)** Color gamut (typical)

Color depth

Calibration Accuracy

Contrast ratio (typical)

Response time (typical)

**Backlight** 

ComfortView<sup>1</sup>

AlienFX™ lighting **Ambient Light Sensor** 

Connectivity

**Adaptive Sync** 

**NVIDIA® Reflex Latency Analyzer** 

Stand adjustability

Stand features

**VESA** mount capability

AC input voltage/frequency/current

Power consumption

Dimensions (HxWxD)

Panel Only

Monitor head with stand (compressed/extended height)

Weight

Panel only (for VESA)

Monitor and cables with full packaging

Color options

Compliance standards

Standard service plan

What's included

AW2521H

62.23cm (24.5")

543.2mm x 302.6mm (21.38" x 11.91")

Fast IPS

Antiglare with 3H hardness

FHD 1920 x 1080 at 360Hz (Native with DP) FHD 1920 x 1080 at 240Hz (Native with HDMI)

178º / 178º

0.283mm x 0.280mm, 90 PPI

16:9

400 cd/m<sup>2</sup>

99% sRGB

16.78 million colors

 $\Delta$ E2000 < 1.5 (average)

1000:1

True 1ms gray-to-gray (Extreme Mode)

LED edgelight system

Yes

Yes. 3 zones (Back, Stand, Power Button)

Yes. Detects ambient light and adjusts the brightness of the monitor accordingly 2x HDMI 2.0, 1x DisplayPort 1.4, 1x USB 3.2(Gen1) upstream port (rear), 2x USB 3.2(Gen1) downstream port (rear), 2x USB 3.2(Gen1) downstream port [Front Bottom, one with NVIDIA® Reflex Latency Analyzer and one with BC1.2 charging capability at 2A(max)], 1x Headphone-out jack (front bottom), 1x Audio Line-out jack (rear)

Yes. NVIDIA® G-SYNC® Certified

Yes

Yes. HDR10

Height adjustable stand up to 130 mm with Height Markers, Tilt (-5°to 21°), Swivel (-20°

to 20°), Pivot (-90° to 90°) Built in cable management

Yes, 100mm x 100mm, with quick release button

100 VAC to 240 VAC / 50 Hz or 60 Hz  $\pm$  3 Hz / 1.2 A (typical)

23W (On Mode) 83W (Max)

0.5W (Standby Mode) 0.3W (Off Mode)

328.2mm x 556.3mm x 84.4mm (12.92" x 21.90" x 3.32")

421.2mm - 526.1mm x 556.3mm x 251.9mm

(16.58" - 20.71" x 21.90" x 9.92")

4.5kg (9.96lb) 12.3kg (27.03lb)

Dark Side of the Moon

Product Safety, EMC and Environmental Datasheets

Dell Regulatory Compliance Home Page

Dell and the Environment

3-year Advanced Exchange Service<sup>2</sup> & Premium Panel Exchange

Monitor Panel, Stand riser, Stand base, Cable Cover, Power Cable, 1 x DisplayPort (DP to DP) Cable, 1 x Mini-DisplayPort (mDP to DP) Cable, 1 x USB 3.2(Gen1) upstream cable, Quick setup guide, Safety Information, Alienware Welcome Card

ComfortView feature reduces blue light emission and optimizes eve comfort.

<sup>&</sup>lt;sup>2</sup>Advanced Exchange Service: Replacement part/unit dispatched, if needed, following completion of phone/online diagnosis Fee charged for failure to return defective unit. Availability varies. Other conditions apply

For a copy of the Limited Hardware Warranty, write Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX 78682 or see Dell.com/warranty

Technical specifications subject to change without prior notice.

Product availability varies by country. Please contact your Dell representative for more information.

Copyright 2020 Dell Inc. All rights reserved. Other trademarks or trade names may be used in this document to refer to either the entities claiming the marks and names or their products Dell disclaims proprietary interest in the marks and names of others. Reproduction in any manner whatsoever without express written permission from Dell Inc. is strictly forbidden