Rocketfish™ 4-Port WirelessHD™ Kit

Model: RF-WHD210 | **SKU:** 2893101

Mount a TV or projector to the wall and hide other home theater devices elsewhere in the same room!

Includes two 4-ft. HDMI cables!



Features

- Supports full 1080p and 3D video resolution
- Wirelessly sends full HDMI-quality signals, with no compression or bit dropping
- Works with HDMI devices such as Blu-ray/DVD players, cable/satellite set-top boxes, gaming consoles, and laptops
- Transmits up to 30 ft. within a single room*
- Transmits in the 60 GHz frequency range for crystal-clear reception and no interference from other wireless devices such as WiFi routers or cordless phones
- Compatible with other WiHD-approved devices to create a wireless video area network (WVAN)
- Sleek design fits most room decor

*Transmitter and receiver are pre-paired and must be in the same room


HDMI™ HIGH-DEFINITION MULTIMEDIA INTERFACE

FULL HD 1080p


WiHD™

Supports 1080p and 3D video, 5.1/7.1 digital surround sound and CEC control

Video








Audio





Rocketfish™ 4-Port WirelessHD™ Kit

Model: RF-WHD210 | **SKU:** 2893101



Wirelessly connect up to 4 HDMI sources to your HD TV or projector!

Use With:

- Ceiling-mounted HD projectors
- Wall-mounted HD TVs
- Any HD HDMI installation within the same room where running an HDMI cable is difficult or unsightly

Package contents

- 60 GHz WirelessHD transmitter
- 60 GHz WirelessHD receiver
- Mounting bracket for receiver
- HDMI cables (2)
- AC power adapter for transmitter
- AC power adapter for receiver
- Remote control
- *Quick Setup Guide*
- *User Guide*



Receiver mounts to a wall or ceiling, or can be placed on a flat surface



Connect up to 4 HDMI devices to the transmitter

Includes two 4 ft. Rocketfish HDMI cables and compact remote for easy control.



Product Specifications

- WirelessHD, HDMI (V1.4a 3D) standards
- 60 GHz frequency
- HDMI input/output interface
- 32-antenna array (integrated ceramic)
- Range of 30 ft. (9.1 m)
- 4-port (CEC pass-through) HDMI port transmitter
- 1-port (CEC pass-through) receiver

- AC power adapter
  AC 90-230 V @60 Hz input
  Transmitter: DC 12V 1.0 A
  Receiver: DC 5V 2.0 A
- CR2025 lithium battery (in remote control)
- Operating temperature: 32°~104°F (0°~40°C) ambient
- Storage temperature: -4°~158°F (-20°~70°C)
- Operating humidity: 10% to 90% (non-condensing)

- Storage humidity: 5% to 90% (non-condensing)
- 1-year limited warranty
- Dimensions
  Transmitter: 7.39 × 6.18 × 2.17 in. (187.6 × 157.0 × 55.2 mm)
  Receiver: 6.06 × 4.72 × 1.89 in. (154.0 × 120.0 × 48.0 mm)
- Weight
  Transmitter: 12.87 oz. (365 g)
  Receiver: 8.54 oz. (242 g)