



User Guide

Features:

- One Pair 5" x 7" / 6" x 8" Three-Way Triaxial Speaker System
- Power Handling: 150 Watts RMS / 300 Watts Peak
- Non-fatiguing Butyl Rubber Surround
- 1" High-Temperature ASV Voice Coil
- Standard 5" x 7" / 6" x 8" Size– Fits OEM Factory Speaker Locations
- Stylish Blue Poly Injection Cone
- 20 oz. Magnet Structure
- 1" Neodymium Film Dome Midrange
- 3/4" Piezo Tweeter
- Impedance: 4 Ohms
- Sensitivity: 90 dB
- Frequency Response: 80 Hz – 20 kHz
- Mounting Depth: 2.25 in (57 mm)
- Includes Speaker Grills, Wires, and Mounting Hardware

Visit Our Website



SCAN ME
PyleUSA.com



Installation Instructions

1. **Turn Off Your Car Battery:** Disconnect the negative (-) terminal to avoid shocks.
2. **Remove Old Speakers:** Take off door panels or grills and unscrew the factory speakers.
3. **Wire the New Speakers:** Connect wires to the new speakers.
Match the positive (+) and negative (-) wires correctly.
4. **Mount the New Speakers:** Insert the speakers into the opening and secure them with the provided screws.
5. **Attach Grills and Test:** Clip on the speaker grills and reconnect the battery.
Play audio to test sound.

California Prop 65 Warning

WARNING:

This product may expose you to chemicals, which is known to the state of California to cause cancer, birth defects and other reproductive harm. Do not ingest.

For more info go to: www.P65warnings.ca.gov



Questions? Comments?

We are here to help!

Phone: (1) 718-535-1800

PyleUSA.com/ContactUs

Cleaning, Maintenance, and Storage

Cleaning:

- Use a dry microfiber cloth to gently wipe off dust from the speaker grills and cones.
- For stubborn dirt, lightly dampen the cloth with water. Do not use solvents or abrasive cleaners.
- Avoid using compressed air, which may damage the cone material.

Maintenance:

- Periodically check wire connections to ensure they remain secure.
- Inspect the speaker surrounds for wear or cracking—especially in hot or humid climates.
- Keep the area around the speakers clean to prevent debris from entering the cone or grill.

Storage (if not installed or during vehicle storage):

- Keep the speakers in a dry, cool environment away from direct sunlight.
- Store in original packaging or wrap in soft cloth to prevent dust accumulation and physical damage.
- Avoid storing near magnets or devices that may affect the speaker's magnetic components.

Safety Precautions

- Do not overload the speakers beyond their rated wattage.
- Avoid installing in locations with excessive moisture or heat.
- Ensure all wiring is insulated and secure to prevent shorts or damage.

Register Product

Thank you for choosing PyleUSA. By registering your product, you ensure that you receive the full benefits of our exclusive warranty and personalized customer support. Complete the form to access expert support and to keep your PyleUSA purchase in perfect condition.

Start Here



Model Number:

PL573BL

PyleUSA.com/pages/register