

## KM 2012 G Gas cooktop with a mono wok burner for special applications.



- Simple controls -single-handed operation via rotary dial control
- Professional design 25 5/8 (650) in (mm) wide stainless steel trough
- Particularly versatile 4 burners incl. 1 mono wok
- Extremely safe GasStop function
- Easy cleaning ComfortClean dishwasher-safe grates

EAN: 4002516354093 / Material number: 11471350 / Old Material Number: 26201250USA

Heating type Fuel type Construction type	
	0.55
Construction type	Gas
Leaders and a star for the second	
Independent of oven	•
Design	
Stainless steel trough	•
Cast iron pot rest (matte black enameled)	•
Ring features	
No. of rings	4
1st cooking zone/cooking area	
Position	front left
Туре	Single wok burner
Max. rating in W	3300
2nd cooking zone/cooking area	
Position	rear left
Туре	Economy burner
Max. rating in W	1100
3rd cooking zone/cooking area	
Position	rear right
Туре	Standard burner
Max. rating in W	1600
4th cooking zone/cooking area	
Position	front right
Туре	Standard burner
Max. rating in W	1600
Control panel	
Operation via knobs	•
Electronic ignition with one-handed operation	•
Cleaning convenience	
Dishwasher-save trivets	•
PerfectClean burner	•
Safety	
GasStop	•
Technical data	
Dimensions (H $\times$ W $\times$ D) in inches (mm)	
Dimensions (width) in in. (mm)	25 5/8 (650)
Height in in. (mm)	3 5/8 (90)
	20 1/2 (520)
Dimensions in mm (depth)	· · _ · _ · _ · _ · _ · _ · _ · _
Cutout dimensions (width) in in. (mm)	22 1/8 (560)
Cutout dimonsions (donth) in in (mm)	19 (480)
Cutout dimensions (depth) in in. (mm)	30 (14)
Weight in lbs. (kg)	
Weight in lbs. (kg) Total connected load in kW	7.60
Weight in lbs. (kg)   Total connected load in kW   Power cord length in in. (m)	7.60 3 (1.2)
Weight in lbs. (kg) Total connected load in kW Power cord length in in. (m) Voltage in V	7.60 3 (1.2) 120
Weight in Ibs. (kg) Total connected load in kW Power cord length in in. (m) Voltage in V Frequency in Hz	7.60 3 (1.2)
Weight in lbs. (kg) Total connected load in kW Power cord length in in. (m) Voltage in V	7.60 3 (1.2) 120



KM 2012 G Gas cooktop with a mono wok burner for special applications.



KM2010G (Installation drawing)

1. Front, 2 Building-in depth, 3. Gas connection R 1/2 - ISO 7-1 (DIN EN 10226), 4. Mains connection box with mains connection cable, L = 2000 mm