

polk.

DRB+

MARINE CERTIFIED
SPEAKER SERIES

POLKAUDIO.COM



polk.

DB+



MARINE CERTIFIED

IP56 rating (water- and dirt-resistant)

Waterproof inner and outer surrounds keep the elements out

UV tolerant cones

Tested for salt-fog, UV and humidity

Everything you love about Polk's Dynamic Balance technology—that rich, clean, full-range sound—is built into the marine-tough, yet ruggedly sophisticated, DB Plus series. And with its universal fit, it can be installed in any vehicle: automobiles, motorcycles, boats, ATVs—you name it.

Features

High Performance Upgrade

Upgrade from your OEM speaker system toward a bigger, fuller, high-performance sound.

Marine Certified

Built to last for cars, boats and ATVs with an IP56 rating and tested for Salt-fog, UV & Humidity.

Universal Fit

Simple drop in installation for any vehicle including cars, boats, ATV's -- you name it.

Zero Tweeter Protrusion

A shallow tweeter design to ensure your factory speaker grille re-installs with ease for a flush, seamless look.

Dynamic Balance Technology

Patented process that guides material selection through rigorous testing that identifies and cancels out unwanted resonant frequencies.



DB+ Series Coaxial and Component Systems Specifications

	DB402	DB522	DB652	DB462	DB572	DB692	DB 5252	DB6502
Type	4" coaxial	5.25" coaxial	6.5" coaxial	4" x 6" coaxial	5" x 7" coaxial	6" x 9" three way	5.25" component	6.5" component
Driver Complement (inches & mm)	4" 101.60 mm	5.25" 133.35 mm	6.5" 165 mm	4" x 6" 101.6 mm x 152.4 mm	5" x 7" 127 mm x 177.8 mm	6" x 9" 152.4 mm x 228.6 mm	5.25" 133.35 mm	6.5" 165 mm
Tweeter Complement (inches & mm)	0.75" 19 mm	0.75" 19 mm	0.75" 19 mm	0.75" 19 mm	0.75" 19 mm	0.75" + 0.5" 19 mm + 13 mm	0.75" 19 mm	0.75" 19 mm
Cutout Dimensions (inches & mm)	4.09" 104 mm	4.76" 121 mm	5.0" 127 mm	4" x 6" 101.6 mm x 152.4 mm	4.92" x 7.15" 125 mm x 181.6 mm	5.97" x 8.80" 151.6 mm x 223.5 mm	4.76" 121 mm	5.0" 127 mm
Mounting Height (inches & mm)	0.22" 5.59 mm	0.31" 8 mm	0.47" 12 mm	0.18" 4.57 mm	0.51" 12.95 mm	0.66" 16.76 mm	0.28" 7.11 mm	0.41" 10.41 mm
Mounting Depth: Top (inches & mm)	1.79" 45.5 mm	1.74" 44.2 mm	1.77" 45 mm	1.81" 46 mm	2.24" 57 mm	3.25" 82.5 mm	1.74" 44.2 mm	1.77" 45 mm
Mounting Depth: Bottom (inches & mm)	2.00" 51 mm	2.01" 51.2 mm	2.12" 54 mm	1.91" 48.6 mm	2.76" 0 mm	3.83" 97.3 mm	2.02" 51.2 mm	2.23" 54 mm
Peak Power Handling	135 W	300 W	300 W	150 W	225 W	450 W	300 W	300 W
Continuous Power Handling	45 W	100 W	100 W	50 W	75 W	150 W	100 W	100 W
Nominal Impedance (ohm)	4	4	4	4	4	4	4	4
Frequency Response (Hz)	60Hz-22kHz	55Hz-22kHz	40Hz-22kHz	50Hz-22kHz	35Hz-22kHz	30Hz-22kHz	50Hz-23kHz	35Hz-23kHz
Grille Height	14.07 mm	17.55 mm	20 mm	n/a	n/a	22.94 mm	17.55 mm	20 mm
Sensitivity (dB)	90	91	92	90	92	93	91	92